NSN 5905-00-080-4162

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-080-4162 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established **Overall Length:** 1.578 inches **Overall Height:** 0.406 inches **Shaft Diameter:** 0.115 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.328 inches **Body Width:** 0.359 inches **Body Height:** 0.313 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.216 inches **Screw Thread Series Designator:** Unf Screw Thready Qty Per Inch (tpi): 28.0 **Terminal Location:**

Lower adjacent side two rows **Mounting Method:**

Electrical Resistance Per Section:

5.000 kilohms single section

Standard bushing

NSN 5905-00-080-4162

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** Demilitarization: No