

NSN 5905-00-080-4796 Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-080-4796 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.609 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 2.562 inches **Shaft Style:** Round **Actuator Type:** Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

82.0 ohms single section

Rotary Actuator Travel In Angular Deg:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

165.0 single section

NSN 5905-00-080-4796

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -30.0 to 30.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -2.0 to 2.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 2 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:** No