Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-080-4896

Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
0.668 inches
Terminal Length:
Between 0.203 inches and 0.233 inches
Overall Height:
Between 0.372 inches and 0.378 inches
Overall Width:
Between 0.213 inches and 0.228 inches
Mounting Hole Diameter:
Between 0.076 inches and 0.078 inches
Shaft Diameter:
Between 0.091 inches and 0.095 inches
Shaft Length:
Between 0.065 inches and 0.085 inches
Body Length:
0.375 inches
0.375 inches
0.375 inches Body Width:
0.375 inches Body Width: Between 0.213 inches and 0.228 inches
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height:
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style:
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type:
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation:
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque:
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque: 5.00 inch-ounces
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque: 5.00 inch-ounces Center To Center Distance Between Terminals:
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: 0.187 inches
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: 0.187 inches
0.375 inches Body Width: Between 0.213 inches and 0.228 inches Body Height: Between 0.372 inches and 0.378 inches Shaft Style: Round, slotted Actuator Type: Single shaft Effective Electrical Rotation In Deg Angular Rotation: 9000.0 Maximum Starting Torque: 5.00 inch-ounces Center To Center Distance Between Terminals: 0.187 inches Lateral Distance Between Mounting Hole Centers: 0.375 inches

Upper adjacent side two rows

NSN 5905-00-080-4896

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
15.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0