

View Online at <https://aerobasegroup.com/nsn/5905-00-080-5117>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 0.484 inches and 0.516 inches

**Mounting Hole Diameter:**

0.125 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

Between 0.109 inches and 0.141 inches

**Mounting Bushing Length:**

0.125 inches

**Body Length:**

0.665 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

9000.0

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.516 inches

**Mounting Facility Quantity:**

1

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0 to 20.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

65.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0