## NSN 5905-00-080-6799

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-080-6799 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.437 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.312 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.219 inches **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.000 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 solder stud Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5905-00-080-6799

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0