## NSN 5905-00-080-9917

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-080-9917 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.790 inches **Overall Height:** Between 0.734 inches and 0.766 inches **Overall Width:** Between 0.245 inches and 0.260 inches **Mounting Hole Diameter:** Between 0.133 inches and 0.139 inches **Shaft Diameter:** Between 0.088 inches and 0.092 inches **Shaft Length:** 0.040 inches **Body Length:** Between 0.734 inches and 0.766 inches **Body Width:** Between 0.245 inches and 0.260 inches **Body Height:** Between 0.734 inches and 0.766 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 7.50 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.776 inches and 0.791 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 

100.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

15120.0

## NSN 5905-00-080-9917

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**