NSN 5905-00-081-5330

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-081-5330

1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.390 inches
Overall Height:
0.530 inches
Mounting Hole Diameter:
0.036 inches
Shaft Diameter:
0.120 inches
Shaft Length:
0.050 inches
Body Length:
1.340 inches
Body Width:
0.290 inches
Body Height:
0.360 inches
Shaft Style:
Round, slotted
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
0.690 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
10.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.330 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
135.0 single section

NSN 5905-00-081-5330

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0