NSN 5905-00-081-5746

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-081-5746

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-30.0 to 30.0
Electrical Resistance:
20.000 ohms
Resistance Tolerance In Percent:
-3.000 to 3.000
Heat Sink Length:
7.000 inches
Heat Sink Width:
5.000 inches
Heat Sink Thickness:
0.040 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0 to 275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
**
Tab, solder lug
Tab, solder lug Reliability Indicator:
Tab, solder lug Reliability Indicator: Not established
Tab, solder lug Reliability Indicator: Not established Terminal Length:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.750 inches
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 6.000 free air
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 6.000 free air Mounting Bushing Diameter:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 6.000 free air Mounting Bushing Diameter: 0.375 inches
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 6.000 free air Mounting Bushing Diameter: 0.375 inches Style Designator:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 6.000 free air Mounting Bushing Diameter: 0.375 inches Style Designator: Axial terminal each end

--

NSN 5905-00-081-5746

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0