## NSN 5905-00-081-6137

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-081-6137
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-200.0/+400.0 first temp coefficient
Electrical Resistance:
5.100 ohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+350.0 temp range of first temp coefficient
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Not established
Terminal Length:
Between 1.375 inches and 2.125 inches
Body Diameter:
Between 0.125 inches and 0.251 inches
Body Length:
Between 0.437 inches and 0.563 inches
Power Dissipation Rating In Watts:
3.000 free air
Cubic Measure (non-core):
0.028 cubic inches
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-prf-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-26/4 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

**Fiig:** A001a0

No

## NSN 5905-00-081-6137

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-26 spec.