Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-081-8090

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# Body Diameter:

0.500 inches

# Shaft Diameter:

0.125 inches

#### Shaft Length:

0.875 inches

### Mounting Bushing Length:

0.250 inches

Body Length:

### 0.453 inches

Shaft Style:

#### Round, slotted

Actuator Type:

#### Single shaft

Nonturn Device Location:

At 3 oclock and at 9 oclock

# Nonturn Device Radius:

0.245 inches

#### Screw Thread Diameter:

0.250 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

#### Mounting Method:

Standard bushing

#### **Electrical Resistance Per Section:**

1.000 megohms single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

### Standard Taper Curve Per Section:

A single section

### **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0