## NSN 5905-00-081-8655

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-081-8655

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0 to 20.0
Electrical Resistance:
0.300 ohms
Resistance Tolerance In Percent:
-3.000 to 3.000
Heat Sink Length:
7.000 inches
Heat Sink Width:
5.000 inches
Heat Sink Thickness:
0.040 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0 to 275.0
Inclosure Method:
Encased
Tarminal Trans.
Terminal Type:
Tab, solder lug
Tab, solder lug
Tab, solder lug  Reliability Indicator:
Tab, solder lug  Reliability Indicator:  Not established
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:  0.312 inches
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:  0.312 inches  Body Diameter:
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:  0.312 inches  Body Diameter:  0.500 inches
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:  0.312 inches  Body Diameter:  0.500 inches  Mounting Bushing Length:
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:  0.312 inches  Body Diameter:  0.500 inches  Mounting Bushing Length:  0.250 inches
Tab, solder lug  Reliability Indicator: Not established  Terminal Length: 0.312 inches  Body Diameter: 0.500 inches  Mounting Bushing Length: 0.250 inches  Body Length:
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:  0.312 inches  Body Diameter:  0.500 inches  Mounting Bushing Length:  0.250 inches  Body Length:  0.500 inches
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:  0.312 inches  Body Diameter:  0.500 inches  Mounting Bushing Length:  0.250 inches  Body Length:  0.500 inches  Power Dissipation Rating In Watts:
Tab, solder lug  Reliability Indicator: Not established  Terminal Length: 0.312 inches  Body Diameter: 0.500 inches  Mounting Bushing Length: 0.250 inches  Body Length: 0.500 inches  Power Dissipation Rating In Watts: 6.000 free air
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length:  0.312 inches  Body Diameter:  0.500 inches  Mounting Bushing Length:  0.250 inches  Body Length:  0.500 inches  Power Dissipation Rating In Watts:  6.000 free air  Mounting Bushing Diameter:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 6.000 free air Mounting Bushing Diameter: 0.375 inches
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.312 inches Body Diameter: 0.500 inches Mounting Bushing Length: 0.250 inches Body Length: 0.500 inches Power Dissipation Rating In Watts: 6.000 free air Mounting Bushing Diameter: 0.375 inches Cubic Measure (non-core):
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length: 0.312 inches  Body Diameter: 0.500 inches  Mounting Bushing Length: 0.250 inches  Body Length: 0.500 inches  Power Dissipation Rating In Watts: 6.000 free air  Mounting Bushing Diameter: 0.375 inches  Cubic Measure (non-core): 0.062 cubic inches

N/a

## NSN 5905-00-081-8655

Inductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0