NSN 5905-00-082-0533

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-082-0533 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 2.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 3.062 inches **Undercut Diameter:** 2.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Body Length:** 2.337 inches **Overall Diameter:** 3.000 inches **Mounting Lip Diameter:** 3.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 358.0 **Maximum Starting Torque:**

2.50 inch-ouncesMaximum Running Torque:1.50 inch-ounces

NSN 5905-00-082-0533

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.010 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
100.0 kilohms 2nd section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00 to 1.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 all sections
Power Dissipation Rating Per Section In Watts:
3.75 free air 1st section
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-082-0533

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0