Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-082-0682

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Overall Length:

0.430 inches

Terminal Length:

0.175 inches

Body Diameter:

0.510 inches

Body Length:

0.255 inches

Overall Diameter:

0.510 inches

Actuator Type:

Flush drive with slot-hole

Maximum Starting Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.190 inches and 0.210 inches

Terminal Location:

Rear end

Mounting Method:

Terminal

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

2.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

285.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Stops



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0