

View Online at <https://aerobasegroup.com/nsn/5905-00-082-1479>

**Section Quantity:**

2

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

1.8750 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.211 inches

**Undercut Diameter:**

1.875 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

2.000 inches

**Shaft Diameter:**

0.625 inches

**Shaft Length:**

0.563 inches

**Body Length:**

1.586 inches

**Overall Diameter:**

2.250 inches

**Mounting Lip Diameter:**

2.0000 inches

**Mounting Lip Depth:**

0.0930 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

356.0

**Maximum Starting Torque:**

2.60 inch-ounces

**Maximum Running Torque:**

1.60 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.001 inches

**Lateral Runout:**

0.006 inches

**Pilot Diameter Runout:**

0.0015 inches

**Shaft Radial Play:**

0.002 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

1.0 kilohms 2nd section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.50 to 0.50 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 all sections

**Power Dissipation Rating Per Section In Watts:**

3.5 free air all sections

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Terminal Type And Quantity:**

6 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0