

View Online at <https://aerobasegroup.com/nsn/5905-00-083-5015>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7600 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

1.188 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Shaft Radial Play:

0.003 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

100.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

65.0 all sections

Test Data Document:

92755-43698 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0