## NSN 5905-00-085-0138

**Section Quantity:** 

Rectangular w/mounting holes

**Body Style:** 

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-085-0138

Reliability Indicator:					
Not established					
Overall Length:					
0.712 inches					
Terminal Length:					
0.172 inches					
Overall Height:					
Between 0.490 inches and 0.510 inches					
Overall Width:					
Between 0.180 inches and 0.230 inches					
Shaft Diameter:					
Between 0.058 inches and 0.098 inches					
Shaft Length:					
0.045 inches					
Body Length:					
0.540 inches					
Body Width:					
Between 0.180 inches and 0.230 inches					
Body Height:					
Between 0.490 inches and 0.510 inches					
Shaft Style:					
Round, slotted					
Actuator Type:					
Single shaft					
Maximum Running Torque:					
5.00 inch-ounces					
Center To Center Distance Between Terminals:					
Between 0.090 inches and 0.110 inches					
Lateral Distance Between Mounting Hole Centers:					
0.520 inches					
Terminal Location:					
Lower adjacent side two rows					
Mounting Method:					
Terminal					
Center To Center Distance Between Terminal Rows:					
0.100 inches					
<b>Electrical Resistance Per Section:</b>					

20.0 kilohms single section

## NSN 5905-00-085-0138

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



	Rotary	Actuator	Travel Ir	n Angular	Deg:
--	--------	----------	-----------	-----------	------

Between 7200.0 and 16200.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

## **Test Data Document:**

81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 pin

**Specification Data:** 

81349-mil-r-27208/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0