NSN 5905-00-085-3550

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-085-3550 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.4380 inches Pilot Length: 0.0620 inches **Overall Length:** 2.094 inches **Undercut Diameter:** 2.062 inches **Undercut Width:** 0.0800 inches **Body Diameter:** 2.875 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Body Length:** 1.338 inches **Overall Diameter:** 3.000 inches **Mounting Lip Diameter:** 3.0000 inches **Mounting Lip Depth:** 0.0930 inches **Mounting Hole/stud Circle Diameter:** 1.750 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

NSN 5905-00-085-3550

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Maximum Starting Torque:
1.00 inch-ounces
Shaft End Play:
0.002 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.0005 inches
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-085-3550

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0