## NSN 5905-00-086-0725

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-086-0725 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.672 inches First Flat Length: Between 0.344 inches and 0.594 inches Flat Height: Between 0.211 inches and 0.221 inches **Body Diameter:** 2.750 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Shaft Length:** Between 0.828 inches and 0.922 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.750 inches **Overall Diameter:** 2.750 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Maximum Starting Torque:** 40.00 inch-ounces **Maximum Stop Torque:** 240.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** Between 0.485 inches and 0.515 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** 

Unef Screw Thready Qty Per Inch (tpi): 32.0

## NSN 5905-00-086-0725

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 310.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab w/screw
Specification Data:
81349-mil-r-22/6 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0