NSN 5905-00-087-0694

Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-087-0694



Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.359 inches First Flat Length: 0.266 inches Flat Height: 0.016 inches **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 2.422 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.531 inches **Overall Diameter:** 1.125 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.0 kilohms single section **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

NSN 5905-00-087-0694

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0