## NSN 5905-00-087-1123

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-087-1123

Section Quantity:  1  Body Style: Rectangular w/mounting holes Reliability Indicator: Not established Overall Length: Between 0.490 inches and 0.510 inches Terminal Length: 0.500 inches Overall Height: Between 0.490 inches and 0.510 inches Overall Width: 0.720 inches Mounting Hole Diameter: 0.078 inches
Body Style: Rectangular w/mounting holes Reliability Indicator: Not established Overall Length: Between 0.490 inches and 0.510 inches Terminal Length: 0.500 inches Overall Height: Between 0.490 inches and 0.510 inches Overall Width: 0.720 inches Mounting Hole Diameter:
Rectangular w/mounting holes  Reliability Indicator:  Not established  Overall Length:  Between 0.490 inches and 0.510 inches  Terminal Length:  0.500 inches  Overall Height:  Between 0.490 inches and 0.510 inches  Overall Width:  0.720 inches  Mounting Hole Diameter:
Reliability Indicator: Not established  Overall Length: Between 0.490 inches and 0.510 inches  Terminal Length: 0.500 inches  Overall Height: Between 0.490 inches and 0.510 inches  Overall Width: 0.720 inches  Mounting Hole Diameter:
Not established  Overall Length: Between 0.490 inches and 0.510 inches  Terminal Length: 0.500 inches  Overall Height: Between 0.490 inches and 0.510 inches  Overall Width: 0.720 inches  Mounting Hole Diameter:
Overall Length: Between 0.490 inches and 0.510 inches Terminal Length: 0.500 inches Overall Height: Between 0.490 inches and 0.510 inches Overall Width: 0.720 inches Mounting Hole Diameter:
Between 0.490 inches and 0.510 inches  Terminal Length: 0.500 inches  Overall Height: Between 0.490 inches and 0.510 inches  Overall Width: 0.720 inches  Mounting Hole Diameter:
Terminal Length: 0.500 inches  Overall Height: Between 0.490 inches and 0.510 inches  Overall Width: 0.720 inches  Mounting Hole Diameter:
0.500 inches  Overall Height:  Between 0.490 inches and 0.510 inches  Overall Width:  0.720 inches  Mounting Hole Diameter:
Overall Height: Between 0.490 inches and 0.510 inches Overall Width: 0.720 inches Mounting Hole Diameter:
Between 0.490 inches and 0.510 inches  Overall Width:  0.720 inches  Mounting Hole Diameter:
Overall Width: 0.720 inches Mounting Hole Diameter:
0.720 inches  Mounting Hole Diameter:
Mounting Hole Diameter:
-
0.078 inches
Shaft Diameter:
0.083 inches
Shaft Length:
Between 0.020 inches and 0.040 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.210 inches and 0.230 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.510 inches and 0.530 inches
Mounting Facility Quantity:
2
Terminal Location:
Left adjacent side single row
Mounting Method:

Unthreaded hole

## NSN 5905-00-087-1123

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
25.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0