NSN 5905-00-087-2732

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-087-2732

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 3.00 to 30.0 Electrical Resistance: 3.000 ohms Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 35.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 3etween 1.370 inches and 1.620 inches 3edoy Length: 3etween 0.470 inches and 0.230 inches 3edoy Length: 3etween 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Skyle Designator:
Electrical Resistance: 3.000 ohms Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 404.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 404.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air
Resistance Tolerance In Percent: 5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 8.000 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Between 0.170 inches and 0.230 inches Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 8.000 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 40.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 40.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Between 0.170 inches and 0.230 inches Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 8.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 8.000 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 340.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 8.000 free air
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Setween 1.370 inches and 1.620 inches Body Diameter: Between 0.470 inches and 0.230 inches Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 8.000 free air
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 350.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: B.000 free air
55.0 to 350.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Between 0.470 inches and 0.560 inches Between 0.470 inches and 0.560 inches Body Length: Between 0.470 inches and 0.560 inches
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: B.000 free air
Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: B.000 free air
Wire lead Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: B.000 free air
Reliability Indicator: Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: B.000 free air
Not established Ferminal Length: Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: B.000 free air
Getween 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: B.000 free air
Between 1.370 inches and 1.620 inches Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: B.000 free air
Body Diameter: Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air
Between 0.170 inches and 0.230 inches Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air
Body Length: Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air
Between 0.470 inches and 0.560 inches Power Dissipation Rating In Watts: 3.000 free air
Power Dissipation Rating In Watts: 3.000 free air
3.000 free air
Style Designator:
Axial terminal each end
Test Data Document:
06481-922465 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No No
Filg:
A001a0