Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-087-4194

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0 to 50.0

## **Electrical Resistance:**

3.320 ohms

## **Resistance Tolerance In Percent:**

-1.000 to 1.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 25.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

#### 275.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 275.0

## **Inclosure Method:**

Encased

#### **Terminal Type:**

## Tab, solder lug

Reliability Indicator:

Not established

## **Terminal Length:**

Between 0.250 inches and 0.374 inches

## **Body Length:**

Between 0.688 inches and 0.812 inches

## Body Width:

Between 0.376 inches and 0.500 inches

## **Body Height:**

Between 0.375 inches and 0.437 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 0.552 inches and 0.572 inches

## **Power Dissipation Rating In Watts:**

6.000 free air

#### Terminal Width:

0.140 inches

## Mounting Hole Size:

Between 0.089 inches and 0.099 inches

#### Cubic Measure (non-core):

0.133 cubic inches

## Style Designator:

Axial terminal (s)

## **Test Data Document:**

81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-18546/1 government specification

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0