## NSN 5905-00-087-4461

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-087-4461

-30.0/430.0 Electrical Resistance: 0.100 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Langth: 0.812 inches Body Langth: 0.812 inches Stoyle de Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shell Life: Na Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 0.100 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.312 inches Power Dissipation Rating in Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No Unit of Measure:	
0.100 ohms  Resistance Tolerance In Percent: 1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/s145.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.312 inches  Body Length: 0.312 inches  Body Length: 0.312 inches  Fower Dissipation Rating In Watts: 0.500 free air  Criticality Code Justification: Test  Style Designator: Avial terminal each end  Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life: N/a  Unit Of Measure:	
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.6.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wive lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Na Unit Of Measure:	
-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Langth: 0.812 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+145.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.312 inches  Body Length:  0.812 inches  Power Dissipation Rating In Watts:  0.500 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.)  Shelf Life:  Na  Unit Of Measure:   Demilitarization:  No  Flig:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+145.0 Inclosure Method: Encapsulated Terminal Type:  Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.312 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.812 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.812 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.812 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	145.0
-55.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.812 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.500 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-55.0/+145.0
Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.312 inches  Body Length: 0.812 inches  Power Dissipation Rating In Watts: 0.500 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fiig:	Inclosure Method:
Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.312 inches  Body Length: 0.812 inches  Power Dissipation Rating In Watts: 0.500 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Fiig:	Encapsulated
Reliability Indicator:  Not established  Body Diameter: 0.312 inches  Body Length: 0.812 inches  Power Dissipation Rating In Watts: 0.500 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Terminal Type:
Note stablished  Body Diameter: 0.312 inches  Body Length: 0.812 inches  Power Dissipation Rating In Watts: 0.500 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter:  0.312 inches  Body Length: 0.812 inches  Power Dissipation Rating In Watts: 0.500 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Reliability Indicator:
0.312 inches  Body Length: 0.812 inches  Power Dissipation Rating In Watts: 0.500 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Filig:	Not established
Body Length:  0.812 inches  Power Dissipation Rating In Watts:  0.500 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Body Diameter:
0.812 inches  Power Dissipation Rating In Watts: 0.500 free air  Criticality Code Justification:  Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	0.312 inches
Power Dissipation Rating In Watts:  0.500 free air  Criticality Code Justification: Test  Style Designator:  Axial terminal each end  Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Length:
O.500 free air  Criticality Code Justification: Test  Style Designator: Axial terminal each end  Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	0.812 inches
Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Power Dissipation Rating In Watts:
Style Designator:  Axial terminal each end  Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.500 free air
Style Designator:  Axial terminal each end  Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Criticality Code Justification:
Axial terminal each end  Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test
Test Data Document:  94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	94756-4430155 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0