NSN 5905-00-087-5640

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-087-5640

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Body Diameter:
0.750 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.156 inches
Body Length:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Double ended shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Tab
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.333 free air single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-00-087-5640

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0