## NSN 5905-00-087-7348

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-087-7348 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.344 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 600.0 ohms all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 all sections

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-6.0 to 6.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

## NSN 5905-00-087-7348

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0