## NSN 5905-00-087-8191

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-087-8191 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.220 inches **Body Diameter:** 0.780 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.780 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.200 inches **Overall Diameter:** 0.780 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 325.0 **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.312 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing

Electrical Resistance Per Section: 2.5 kilohms single section

NSN 5905-00-087-8191 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
335.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
30.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0