Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-087-9692

View Online a	t https://aerobasegroup.com/nsn/5905-00-087-9692
Section Quar	ntity:
1	
Body Style:	
Cylindrical	
Reliability Inc	dicator:
Not establishe	łd
Body Diamet	er:
0.785 inches	
Body Length	:
0.422 inches	
Actuator Typ	e:
Flush drive wi	th slot-hole
Effective Elec	ctrical Rotation In Deg Angular Rotation:
240.0	
Terminal Loc	ation:
Rear end	
Mounting Me	thod:
Tab	
Features Pro	vided:
Grounded con	itact arm
Electrical Res	sistance Per Section:
100.0 ohms si	ngle section
Rotary Actua	tor Travel In Angular Deg:
240.0	
Ambient Tem	purature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single s	ection
Power Dissip	ation Rating Per Section In Watts:
2.0 free air sin	igle section
Resistance T	olerance Per Section In Percent:
-20.0 to 20.0 s	single section
Actuator Trav	vel Control Feature:
Stops	
Ambient Tem	purature In Deg Celsius Per Section At Full Rated Power:
55.0 single se	ction
Standard Tap	per Curve Per Section:
A single section	n
Terminal Typ	e And Quantity:
2 tab, solder l	lug
Shelf Life:	
N/a	
Unit Of Meas	ure:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0