NSN 5905-00-088-0171

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-088-0171 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.938 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.375 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.969 inches **Shaft Style:** Round, slotted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.438 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, double throw, three positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:**

Rear end

Mounting Method:

Standard bushing

NSN 5905-00-088-0171

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Switch
Electrical Resistance Per Section:
200.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
20.0 to 20.0 single section
Switch Current Type And Rating In Amps:
3.000 ac and 3.000 dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0