

View Online at <https://aerobasegroup.com/nsn/5905-00-088-0939>**Section Quantity:**

1

**Body Style:**

Cylindrical tab/flange mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.266 inches

**Mounting Hole Diameter:**

0.136 inches

**Body Length:**

0.813 inches

**Actuator Type:**

Flush drive with slot-hole

**End Application:**

Emory s. Land class as; whidbey island class lsd; tarawa class lha; iwo jima class lph; forrestal class cv; kidd class ddg; nimitz class cvn; ticonderoga class cg (47); surgeon class ssn (637)

**Lateral Distance Between Mounting Hole Centers:**

1.000 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Grounded contact arm

**Electrical Resistance Per Section:**

4.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0