Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-088-1106

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

1.320 inches

Overall Height:

0.320 inches

Overall Width:

0.190 inches

Mounting Hole Diameter:

0.088 inches

Shaft Diameter:

0.070 inches

Shaft Length:

0.115 inches

Body Length:

1.250 inches

Body Width:

0.190 inches

Body Height:

0.320 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

1.000 megohms single section

Rotary Actuator Travel In Angular Deg:

7920.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -300.0/+300.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0