

View Online at <https://aerobasegroup.com/nsn/5905-00-088-1500>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

Between 2.224 inches and 2.316 inches

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.750 inches

**Mounting Bushing Length:**

0.312 inches

**Body Length:**

Between 1.443 inches and 1.473 inches

**Overall Diameter:**

1.078 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

0.70 inch-ounces

**Maximum Running Torque:**

0.60 inch-ounces

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.250 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Standard bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

2.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.50 to 0.50 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

80.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0