

View Online at <https://aerobasegroup.com/nsn/5905-00-088-2597>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 1.9360 inches and 1.9370 inches

**Pilot Length:**

Between 0.0290 inches and 0.0320 inches

**Overall Length:**

Between 1.217 inches and 1.260 inches

**Undercut Diameter:**

Between 1.9375 inches and 1.9385 inches

**Undercut Width:**

Between 0.0700 inches and 0.0900 inches

**Body Diameter:**

Between 1.990 inches and 2.010 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

Between 0.198 inches and 0.218 inches

**Body Length:**

Between 0.990 inches and 1.010 inches

**Overall Diameter:**

Between 2.125 inches and 2.151 inches

**Mounting Lip Diameter:**

Between 1.9900 inches and 2.0100 inches

**Mounting Lip Depth:**

Between 0.0680 inches and 0.0850 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 319.0 and 321.0

**Maximum Starting Torque:**

0.60 inch-ounces

**Shaft End Play:**

0.006 inches

**Lateral Runout:**

0.001 inches

**Pilot Diameter Runout:**

0.001 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

1.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-30.0/+30.0 single section

**Power Dissipation Rating Per Section In Watts:**

4.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-1.0 to 1.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Test Data Document:**

81349-mil-r-8903 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

12 solder stud

**Specification Data:**

81349-mil-r-8903 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

1-000-0