NSN 5905-00-088-2743

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-088-2743 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.9370 inches Pilot Length: 0.0320 inches **Overall Length:** 1.000 inches **Undercut Diameter:** 1.937 inches **Undercut Width:** 0.0800 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.218 inches **Body Length:** 1.000 inches **Overall Diameter:** 2.000 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0850 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:**

Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:**

0.60 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

NSN 5905-00-088-2743

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.006 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50 to 0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-30.0 to 30.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-1.0 to 1.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
81349-mil-r-8903 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 turret
Specification Data:
81349-mil-r-8903 government specification

Unit Of Measure:

Shelf Life:

N/a

NSN 5905-00-088-2743

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0