Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-088-3220

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.312 inches **Overall Height:** Between 0.297 inches and 0.328 inches **Overall Width:** Between 0.270 inches and 0.290 inches **Mounting Hole Diameter:** 0.088 inches Shaft Diameter: Between 0.109 inches and 0.141 inches Shaft Length: Between 0.047 inches and 0.078 inches **Body Length:** Between 1.234 inches and 1.266 inches **Body Width:** Between 0.270 inches and 0.290 inches **Body Height:** Between 0.297 inches and 0.328 inches Shaft Style: Round, slotted Actuator Type: Single shaft Lateral Distance Between Mounting Hole Centers: Between 0.990 inches and 1.010 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 200.0 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

NSN 5905-00-088-3220

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-500.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0