NSN 5905-00-088-3355

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-088-3355

Tempurature Coefficient Of Resistance in Ppm Per Deg Celsius: -500.0 to 200.0 Electrical Resistance: 196.000 ohms Resistance Tolerance in Percent: -1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire laad Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Length: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating in Watts: 0.500 free air Unpackaged Unit Weight:
Electrical Resistance: 196.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 185.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
196.000 ohms Resistance Tolerance In Percent: -1,000 to 1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,375 inches and 1,625 inches Body Diameter: Between 0,157 inches and 0,250 inches Body Length: Between 0,531 inches and 0,656 inches Power Dissipation Rating In Watts: 0,500 free air Unpackaged Unit Weight:
Resistance Tolerance In Percent: -1,000 to 1,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 165.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Between 1.375 inches and 1.625 inches Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Body Diameter: Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Between 0.157 inches and 0.250 inches Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Body Length: Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Between 0.531 inches and 0.656 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight:
0.500 free air Unpackaged Unit Weight:
Unpackaged Unit Weight:
0.04 grains
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-10509/2 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No No

Fiig: A001a0