

View Online at <https://aerobasegroup.com/nsn/5905-00-088-5589>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Mounting Hole Diameter:

Between 0.073 inches and 0.113 inches

Shaft Diameter:

Between 0.055 inches and 0.065 inches

Shaft Length:

0.030 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.171 inches and 0.197 inches

Body Height:

Between 0.490 inches and 0.510 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

15120.0

Lateral Distance Between Mounting Hole Centers:

0.530 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

15120.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

200.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

10001-59a5a267-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0