Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-089-1826

### Section Quantity:

1

Body Style:

Cylindrical servo mounted

### **Reliability Indicator:**

Not established

### **Pilot Diameter:**

2.8750 inches

#### **Pilot Length:**

0.0620 inches

### **Overall Length:**

2.288 inches

### Undercut Diameter:

2.875 inches

#### **Undercut Width:**

0.0800 inches

# Body Diameter:

\_\_\_\_\_

# 3.000 inches

Angle Of Mounting Hole In Deg:

90.0

## Angle Between Centerlines Of Mounting Holes In Deg:

120.0

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.438 inches

#### **Body Length:**

1.850 inches

### **Overall Diameter:**

3.600 inches

### Mounting Lip Diameter:

3.0000 inches

#### Mounting Lip Depth:

0.0930 inches

## Mounting Hole/stud Circle Diameter:

1.750 inches

### Shaft Style:

Round

### Shaft Bearing Type:

Ball

### Actuator Type:

Single shaft



Effective Electrical Rotation In Deg Angular Rotation:

360.0

### **Maximum Starting Torque:**

0.50 inch-ounces

### Shaft End Play:

0.001 inches

### Shaft Runout:

0.001 inches

#### Lateral Runout:

0.0015 inches

### **Pilot Diameter Runout:**

0.005 inches

### Shaft Radial Play:

0.001 inches

### Screw Thread Diameter:

0.164 inches

### **Screw Thread Series Designator:**

Unc

### Screw Thready Qty Per Inch (tpi):

32.0

# Mounting Facility Quantity:

#### 3

## **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Clamp ring and threaded hole

### **Electrical Resistance Per Section:**

20.0 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

360.0

### **Function Conformity Tolerance Per Section:**

-0.20 to 0.20 single section

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### **Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

# Function Conformity Per Section:

Single section independent linearity

## **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

### **Actuator Travel Control Feature:**

Continuous motion

# Function Characteristic Per Section:

Single section linear



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

# Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A002a0