NSN 5905-00-089-1826

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-089-1826 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 2.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 2.288 inches **Undercut Diameter:** 2.875 inches **Undercut Width:** 0.0800 inches **Body Diameter:** 3.000 inches **Angle Of Mounting Hole In Deg:** 90.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.438 inches **Body Length:** 1.850 inches **Overall Diameter:** 3.600 inches **Mounting Lip Diameter:** 3.0000 inches **Mounting Lip Depth:** 0.0930 inches **Mounting Hole/stud Circle Diameter:** 1.750 inches **Shaft Style:** Round **Shaft Bearing Type:**

Ball **Actuator Type:**

Single shaft

NSN 5905-00-089-1826

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
0.50 inch-ounces
Shaft End Play:
0.001 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.0015 inches
Pilot Diameter Runout:
0.005 inches
Shaft Radial Play:
0.001 inches
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring and threaded hole
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.20 to 0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:

Single section linear

NSN 5905-00-089-1826

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Ambient	Tempurature	In Deg	Celsius	Per S	ection A	At Full I	Rated	Power:

25.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0