NSN 5905-00-089-8749

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-089-8749 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.093 inches **Shaft Length:** 0.075 inches **Body Length:** 0.375 inches **Body Width:** 0.185 inches **Body Height:** 0.375 inches Shaft Style: Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Lateral Distance Between Mounting Hole Centers:** 0.375 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:**

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

9000.0

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

NSN 5905-00-089-8749

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No