

View Online at <https://aerobasegroup.com/nsn/5905-00-089-9621>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.6250 inches

Pilot Length:

0.0570 inches

Overall Length:

3.430 inches

Undercut Diameter:

0.675 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.880 inches

Shaft Diameter:

0.1248 inches

Shaft Length:

0.380 inches

Body Length:

3.112 inches

Overall Diameter:

0.880 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0570 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3150.0

Maximum Starting Torque:

1.20 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Terminal Location:

Rear end

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

10.0 kilohms 1st section

Rotary Actuator Travel In Angular Deg:

3150.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 all sections

Power Dissipation Rating Per Section In Watts:

0.1 free air all sections

Resistance Tolerance Per Section In Percent:

-1.0 to 1.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0