## NSN 5905-00-097-1149

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-097-1149

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.672 inches
Terminal Length:
0.500 inches
Body Diameter:
Between 0.297 inches and 0.329 inches
Body Length:
Between 0.172 inches and 0.204 inches
Overall Diameter:
Between 0.297 inches and 0.329 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Stop Torque:
8.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.190 inches and 0.210 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
500.000 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.090 inches and 0.110 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0 to 70.0 single section
Power Dissipation Rating Per Section In Watts:

0.5 free air single section

## NSN 5905-00-097-1149

Yes - demil/mli

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Reference Number Differentiating Characteristics:
Navord od41152
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: