Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-097-3644

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.500 inches

#### Shaft Diameter:

0.110 inches

- Shaft Length:
- 0.070 inches

Body Length:

#### 1.250 inches

Body Width:

# 0.190 inches

**Body Height:** 

0.320 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

#### Center To Center Distance Between Terminals:

0.900 inches

#### Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Terminal and unthreaded hole

#### **Electrical Resistance Per Section:**

20.000 kilohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.700 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0 to 150.0 single section

#### Power Dissipation Rating Per Section In Watts:

1.0 free air single section



#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A002a0