

View Online at <https://aerobasegroup.com/nsn/5905-00-097-7501>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.9688 inches

Pilot Length:

0.0620 inches

First Flat Length:

0.344 inches

Flat Height:

0.094 inches

Undercut Diameter:

0.9688 inches

Undercut Width:

0.0620 inches

Body Diameter:

1.093 inches

Shaft Diameter:

0.1248 inches

Shaft Length:

0.500 inches

Body Length:

0.437 inches

Mounting Lip Diameter:

1.0620 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.0025 inches

Shaft Radial Play:

0.0025 inches

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

3.5 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+300.0 single section

Power Dissipation Rating Per Section In Watts:

0.3 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0