

View Online at <https://aerobasegroup.com/nsn/5905-00-098-5931>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.891 inches

**Body Diameter:**

Between 1.625 inches and 1.687 inches

**Shaft Diameter:**

Between 0.248 inches and 0.251 inches

**Shaft Length:**

Between 0.984 inches and 1.016 inches

**Mounting Bushing Length:**

Between 0.484 inches and 0.516 inches

**Body Length:**

0.875 inches

**Overall Diameter:**

1.968 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

Between 0.516 inches and 0.547 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:**

4.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-3.0 to 3.0 single section

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0 to 20.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0