## NSN 5905-00-098-9131

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-098-9131

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:		
-30.0 to 30.0		
Electrical Resistance:		
2.150 kilohms		
Resistance Tolerance In Percent:		
-1.000 to 1.000		
Ambient Tempurature In Deg Celsius At Full Rated Power:		
25.0		
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:		
275.0		
Tempurature Range Of Tempurature Coefficient In Deg Celsius:		
-55.0 to 275.0		
Inclosure Method:		
Encased		
Terminal Type:		
Tab, solder lug		
Reliability Indicator:		
Established		
Reliability Failure Rate Level In Percent:		
0.010		
Terminal Length:		
0.312 inches		
Body Length:		
Between 0.688 inches and 0.812 inches		
Body Width:		
Between 0.376 inches and 0.500 inches		
Body Height:		
Between 0.375 inches and 0.437 inches		
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:		
0.562 inches		
Power Dissipation Rating In Watts:		
6.000 free air		
Terminal Width:		
0.140 inches		
Mounting Hole Size:		
0.094 inches		
Cubic Measure (non-core):		
0.133 cubic inches		
Style Designator:		
Axial terminal (s)		
Test Data Document:		

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-00-098-9131

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Specif	fication	Data:

81349-mil-r-39009/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0