## NSN 5905-00-098-9649

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-098-9649

**Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.688 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.391 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 3.800 kilohms single section **Rotary Actuator Travel In Angular Deg:** 340.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section

**Power Dissipation Rating Per Section In Watts:** 

5.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

## NSN 5905-00-098-9649

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: