NSN 5905-00-098-9666

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-098-9666 **Section Quantity: Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Overall Length:** 3.250 inches First Flat Length: 0.344 inches Flat Height: 0.216 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 0.500 inches **Body Length:** 2.750 inches **Overall Diameter:** 3.369 inches **Mounting Hole/stud Circle Diameter:** 1.750 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 20.0 **Mounting Facility Quantity:**

Terminal Location:

Radially positioned over less than half the circumference

NSN 5905-00-098-9666

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
320.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
100.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0