## NSN 5905-00-099-2034

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-099-2034

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.300 inches
Terminal Length:
0.500 inches
Overall Height:
0.812 inches
Overall Width:
0.312 inches
Mounting Hole Diameter:
0.089 inches
Shaft Diameter:
0.050 inches
Shaft Length:
0.125 inches
Body Length:
1.250 inches
Body Width:
0.312 inches
Body Height:
0.280 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
8.00 inch-ounces
Center To Center Distance Between Terminals:
0.700 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole and terminal

NSN 5905-00-099-2034 Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:
0.100 inches
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
50.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
70.0 to 70.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0