

View Online at <https://aerobasegroup.com/nsn/5905-00-099-9606>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.156 inches

Body Diameter:

0.969 inches

Shaft Diameter:

Between 0.125 inches and 0.250 inches

Shaft Length:

Between 0.750 inches and 1.125 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.000 inches

Overall Diameter:

1.265 inches

Shaft Style:

Round

Actuator Type:

Dual concentric

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

20.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 all sections

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-1000.0 to 1000.0 all sections

Power Dissipation Rating Per Section In Watts:

0.3 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

55.0 all sections

Standard Taper Curve Per Section:

A all sections

Test Data Document:

28480-a2100-3014-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0