NSN 5905-00-100-1692

Inductive Wire Wound Fixed Resistor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5905-00-100-1692 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -260.0 to 260.0-260.0 to 260.0 |
| Electrical Resistance: |
| 350.000 ohms350.000 ohms |
| Resistance Tolerance In Percent: |
| -5.000 to 5.000-5.000 to 5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.025.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| Not rated |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0 to 275.0-55.0 to 275.0 |
| Inclosure Method: |
| Encapsulatedencapsulated |
| Terminal Type: |
| Ferruleferrule |
| Reliability Indicator: |
| Not establishednot established |
| Body Diameter: |
| Between 1.000 inches and 1.312 inches |
| Body Length: |
| Between 6.375 inches and 6.500 inches |
| Power Dissipation Rating In Watts: |
| 86.000 free air |
| Cubic Measure (non-core): |
| 13.396 cubic inches |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-26/1 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A001a0